

LIMIT SWITCH



HLS-1



HLS-2

HLS-3



Solid and beautiful design.
 Aluminium die cast housing and powder coated.
 Bolts on visual position indicator secure waterproof.
 "Quick-Set" cam spring loaded splined cam.
 Need no to readjust after initial setting.
 Multi point terminal strip.
 Standard 8 points and enough strips for connection.
 Dual cable entries : 2 x 1/2" NPT or 2 x 3/4" PF
 Easy mounting.
 NAMUR standard stainless steel shaft and bracket.

Model	HLC-1		HLC-2		HLC-3	
	Standard	Option	Standard	Option	Standard	Option
Enclosure Explosion Proof	IP 67		IP 67		IP 67 EXED 2 B T6 (EN50014/50018)	
Temperature	-25°C ~ 85°C					
Cable Entry	2 x 1/2" NPT	PT1/2, PF1/2 M20, PG13.5	2 x 1/2" NPT	PT1/2, PF1/2 M20, PG13.5	2 x 1/2" NPT	PT1/2, PF1/2 M20, PG13.5
Terminal Strips	8	-	8	9 ~ 24	8	9 ~ 24
Position	0 ~ 90°	0 ~ 180°	0 ~ 90°	0 ~ 180°	0 ~ 90°	0 ~ 180°
Indicator	Open - Yellow; Close - Red					
Switches	Mechanical Swither, Proximity Sensor					

Ordering Information

